

Claims

- [c1] 1. An apparatus for supporting a hand held liquid dispensing device comprising:
a first support member for receiving a nozzle portion of the dispensing device; and
a second support member for holding a container, the first and second support members being spaced from each other in substantial axial alignment and connected to a frame member for connection to a supporting structure.
- [c2] 2. The apparatus as defined in Claim 1 wherein the first support member includes a cavity.
- [c3] 3. The apparatus as defined in Claim 1 wherein the second support member is pivotably connected to the frame member.
- [c4] 4. The apparatus as defined in Claim 1 wherein there are two oppositely disposed first support members connected to the frame member.
- [c5] 5. The apparatus as defined in Claim 1 wherein the first support member is defined by a platform having a cavity for placement of a dispenser nozzle therein.

- [c6] 6. The apparatus as defined in Claim 1 wherein the second support member is defined by a foot portion, the foot portion supported by the frame and pivotally connected to the frame member.
- [c7] 7. The apparatus as defined in Claim 6 wherein the foot portion includes a concave portion for receiving a bottle.
- [c8] 8. The apparatus as defined in Claim 1 wherein there are two oppositely disposed second support members connected to the frame member, the frame member defined by a first portion extending in a first direction and a second portion extending essentially at right angles to the first portion, the second portion connected to the two oppositely disposed second support members.
- [c9] 9. The apparatus as defined in Claim 8 wherein the frame member is composed of rod members.
- [c10] 10. The apparatus as defined in Claim 1 wherein the cavity includes a passage constructed and arranged to permit passage of the nozzle portion therethrough.
- [c11] 11. A combined hand held liquid dispensing device and apparatus for supporting the device comprising:
a liquid dispensing device;
a first support member receiving a nozzle portion of the

dispensing device; and
a second support member for holding a container, the
first and second support members being spaced from
each other in substantial axial alignment and connected
to a frame member for connection to a supporting structure.

- [c12] 12. The apparatus as defined in Claim 11 wherein the first support member includes a cavity.
- [c13] 13. The apparatus as defined in Claim 11 wherein the second support member is pivotably connected to the frame member.
- [c14] 14. The apparatus as defined in Claim 11 wherein there are two oppositely disposed first support members connected to the frame member.
- [c15] 15. The apparatus as defined in Claim 11 wherein the first support member is defined by a platform having a cavity for placement of a dispenser nozzle therein.
- [c16] 16. The apparatus as defined in Claim 11 wherein the second support member is defined by a foot portion, the foot portion supported by the frame and pivotally connected to the frame member.
- [c17] 17. The apparatus as defined in Claim 16 wherein the

foot portion includes a concave portion for receiving a bottle.

[c18] 18. The apparatus as defined in Claim 11 wherein there are two oppositely disposed second support members connected to the frame member, the frame member defined by a first portion extending in a first direction and a second portion extending essentially at right angles to the first portion, the second portion connected to the two oppositely disposed second support members.

[c19] 19. The apparatus as defined in Claim 18 wherein the frame member is composed of rod members.

[c20] 20. The apparatus as defined in Claim 11 wherein the cavity includes a passage constructed and arranged to permit passage of the nozzle portion therethrough.